

Overview

Purpose

To provide an overview of and user guide for the emsTradePoint API services.

Document Control

Record of version history.

Version	Date	Description
0.1	21/05/2018	Initial Draft
1.0	07/06/2018	Published document
1.1	26/06/2018	Included missing information for invoking OAuth2.0 tokens
1.2	10/08/2018	Included sample code for generating OAuth2.0 token
1.3	03/12/2018	Updated explanation for 429 error
1.4	09/02/2020	Updated oauth description, endpoint table, removed ruby samples

Document Approval

Approval for the current version.

Version	Date	Approved by
1.4	10/02/2021	Kerry Wilkins

If you have any queries regarding the content of this document, please contact the emsTradePoint Service Desk on either supportdesk@emstradepoint.co.nz or (04) 590-6692.

Request URIs and HTTP Headers

Service URIs

The base feed URI is made up of the domain + API version, as follows:

Production Domain | <https://exchange.emsTradepoint.co.nz>

UAT Domain | <https://uat-exchange.emsTradepoint.co.nz>

API Version | /data/v1

The base will be followed by an endpoint indicating a specific request or data set, i.e. /ticker, /orders, /trades. Each endpoint will have optional filters that may be used to refine a response.

Authentication

The emsTradepoint Exchange utilises OAuth 2.0 authentication, where credentials are supplied as a JSON payload and an access token is provided that must be provided with all data requests.

B2B Authentication

The requesting/participant web server will need to call the following to request an access token:

<https://{etpDomain}/oauth/token>

The following image demonstrates the JSON payload for both request and response. Note: the client_id and client_secret will be provided at the time of subscribing to the API suite.

```
1 POST [hostname]/oauth/token
2 // request payload for etp authentication
3 {
4   'payload': {
5     'grant_type': 'password',
6     'username': strUsername
7     'password': strPassword,
8     'client_id': strClientId,
9     'client_secret': strClientSecret
10  }
11 }
12
13 // response payload for authenticated user
14 {
15   'token_type': 'bearer',
16   'access_token': strAccessToken,
17   'refresh_token': strRefreshToken,
18   'created_at': strDateTime,
19   'expires_in': 7200
20 }
```

Third Party Authentication

Where a third party client is requesting an access token, that client should call the following URI:

<https://{etpDomain}/oauth/authorize>

Calling this URI will open an emsTradePoint interface which prompts the user to enter their username and password. On submission, the credentials are validated by the emsTradePoint authentication server. If successful, the authentication server will provide an access token that is valid for 2 hours.

In the instance where a third party client is requesting an access token, a callback URI must be registered with the exchange which will redirect the client to a specific URL/web page after authentication.

<https://{yourDomain}/oauth/callback>

Dedicated API Accounts

On request, the emsTradePoint Team can provide a ‘read-only’ account where the password does not expire.

Endpoint List

Company Info	<p><i>GET /v1/companies/ours</i> Returns your company_id and user_id of your colleagues which can be used as optional filters for other endpoints.</p>
Products	<p><i>GET /v1/products</i> Returns a list of active products available to trade on. Filters are available to refine the list.</p> <p><i>GET /v1/products/[id]</i> Returns detail of the identified product, including bids/offers that make up the price stack.</p>
Orders	<p><i>GET /v1/orders</i> Returns a list of gas orders that have been placed on the Exchange. Filters are available to refine the list.</p> <p><i>GET /v1/orders/nzu</i> Returns a list of carbon orders that have been placed on the Exchange. Filters are available to refine the list.</p> <p><i>PATCH /v1/withdraw/all</i> Enables the user to withdraw all live orders (both bids and offers) for the requesting company.</p>
Bids	<p><i>POST /v1/bids</i></p>

	<p>Submits a new bid to the stack. Bids terms can be submitted either as a JSON payload or in the URL.</p> <p><i>GET /v1/bids/[id]</i> Returns details for a known id.</p> <p><i>PATCH /v1/bids/[id]/withdraw</i> Enables the requestor to withdraw a bid with a known id.</p>
Offers	<p><i>POST /v1/offers</i> Submits a new offer to the stack. Offer terms can be submitted either as a JSON payload or in the URL.</p> <p><i>GET /v1/offers/[id]</i> Returns details for a known id.</p> <p><i>PATCH /v1/offers/[id]/withdraw</i> Enables the requestor to withdraw an offer with a known id.</p>
Trades	<p><i>GET /v1/trades</i> Returns a list of gas trades formed on the Exchange. Filters available to refine the list.</p> <p><i>GET /v1/trades/nzu</i> Returns a list of gas trades formed on the Exchange. Filters available to refine the list.</p>
Ticker	<p><i>GET /v1/ticker</i> Returns the 20 latest transactions (trades / orders / both) on the Exchange.</p> <p><i>GET /v1/ticker/trades</i> Returns the 20 latest trades on the Exchange.</p> <p><i>GET /v1/ticker/orders</i> Returns the 20 latest orders (either bids or offers) on the Exchange.</p>
Markets	<p><i>GET /v1/markets</i> Returns the current state of the product markets; On The Day (OTD), Day Ahead (DA), Carbon (NZU).</p>
Indices	<p><i>GET /v1/index</i> Returns the latest monthly and quarterly indices (FRMI/FRQI) for the gas products. Filters are available to request a specific date range.</p>

	<p><i>GET /v1/index/nzu</i></p> <p>Returns the latest monthly and quarterly indices (ECMI/ECQI) for the carbon product. Filters are available to request a specific date range.</p>
--	---

Service Filters

By default, each GET request will return the latest data for the endpoint with default pagination of 30 records. Many of the endpoints provided will allow additional filtering to replicate existing functionality available through the web application.

API Documentation

Live API documentation and a test interface can be found on the following URL:

<https://uat-exchange.emstradepoint.co.nz/api/docs>

The documentation provides current API schemas for the requests and responses. If you wish to run beta testing on the API suite with live data, please contact emsTradePoint to arrange a temporary account for the user acceptance platform.

Response Headers and Data

The following status codes are supported by the emsTradePoint API suite.

HTTP Status	HTTP Headers	HTTP Body and explanation
200	Access-Control-Allow-Origin: Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] ETag: Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	<pre>{ [data with one or more property] }</pre> <p><i>A successful GET request for data or PATCH request to update data. One or more data properties will be present containing data.</i></p>
201	Access-Control-Allow-Origin:	<pre>{ [data with one or more property] }</pre>

	Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] ETag: Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	} <p><i>A successful POST request / submission of data. One or more data properties will be present containing data.</i></p>
400	Access-Control-Allow-Origin: Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	{ "error": [message identifying problem input value] } <p><i>The service client's request has invalid inputs, e.g. incorrect date format, text in place of integer.</i></p>
401	Access-Control-Allow-Origin: Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	{ "error": [authentication specific message] } <p><i>The service client failed to include a current or valid authentication token in the request</i></p>
422	Access-Control-Allow-Origin:	{ "Error": "Validation failed: [detail of failed criterion]" }

	Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	} <p><i>The service failed due to a validation error; exceeded exposure/trader limit, incorrect user/organisation role, etc).</i></p>
429	Access-Control-Allow-Origin: Access-Control-Request-Method: Cache-Control: Connection: Content-Length: Date: [date and time] Server: Status: Strict-Transport-Security: Vary: X-Request-Id: X-Runtime: X-Version:	{ "Error": "Rate Limit Exceeded" } <p><i>The service failed due to a validation error; exceeded current 'requests per minute' limit for the endpoint).</i></p>